

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/005910 A1

(51) International Patent Classification⁷: **G01N 27/447**,
B01L 3/00, B01D 57/02

(74) Agents: **MAGGS, Michael, Norman et al.**; Kilburn &
Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(21) International Application Number:
PCT/GB2003/002926

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 8 July 2003 (08.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0215779.0 8 July 2002 (08.07.2002) GB

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **DELTA-
DOT LIMITED** [GB/GB]; 47D Princes Gardens, London
SW7 2PE (GB).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **HASSARD, John**
[GB/GB]; Deltadot Ltd, 47D Princes Gardens, London
SW7 2PE (GB). **MCKIGNEY, Ed** [GB/GB]; Deltadot
Ltd, 47D Princes Gardens, London SW7 2PE (GB).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MATERIAL SEPARATION DEVICE



(57) Abstract: A separating device for use in separating electrically charged components e.g. by electrophoresis comprises a channel branched at a branch point to provide a main feed channel (105) connected to at least two subsidiary channels (110, 115). In use, different components (120, 125, 130) show differential migration along the feed channel (105) so they can be separated into different subsidiary channels (110, 115) at the branch point. To support this separation, the separating device is provided with switchable voltage control means for controlling local voltages in the region of the branch point to provide potential differences of opposing polarity along the respective subsidiary channels (110, 115) such that a component to be separated (125) can be caused to migrate from the feed channel into a different subsidiary channel (115) from one or more other components.

MATERIAL SEPARATION DEVICE

5 The present invention relates to a device and to a method for separating materials (e.g. biomolecules). It finds particular although not exclusive application in microchannel voltage switching, for instance for use in electrophoresis.

10 Electrophoresis is a technique known for use in the laboratory to separate charged entities such as molecules. For example, DNA fragments can be separated out in this way. If an electric current is applied to a sample carried in a microchannel, the sample can be caused to migrate along the microchannel. In doing so, different constituents will migrate at different speeds so that the
15 sample will separate out into constituent molecular bands positioned at varying distances along the microchannel.

The invention is not limited to molecular separations using electrophoresis, and is equally applicable to the separation of molecules or other components which
20 are flowing in some other way along a channel. In the preferred embodiment, however, we are typically interested in the separation of DNA fragments, RNA fragments and/or proteins, with the separation and/or analysis being carried out in real-time.

25 A branched microchannel is, as its name suggests, a channel which branches into more than one channel. As the constituent molecular bands of a sample migrate along the microchannel, any one band will reach the branch point at a

particular time. By applying an appropriately directed and timed potential difference at the branch point, the band currently migrating past that branch point can be selectively switched to migrate into a side channel.

- 5 A problem arises with this known arrangement when there is a need to change the potential difference at the branch point relatively rapidly, for instance to switch the next constituent molecular band into a different channel. There is a risk that at least the tail end of the constituent molecular band which has just been switched into a side channel will start to migrate back to the branch point
- 10 and may leave the side channel again. Alternatively, the leading edge of the following constituent molecular band may start to follow the previous band into the same side channel. These effects can lead to cross-contamination of the separated constituent molecular bands.
- 15 According to a first embodiment of the present invention, there is provided a separating device for separating components flowing along a channel, the device comprising a main channel branched at a branch point, connected to at least two subsidiary channels, and switchable voltage control means for controlling a voltage in the region of the branch point to provide potential
- 20 differences of opposing polarity along subsidiary channels such that components to be separated are caused to flow from the main channel into a selected subsidiary channel.

For instance the voltage control means can be arranged to provide a short

25 section along a first subsidiary channel which has a negative potential difference in a direction away from the branch point, and a short section along a second subsidiary channel which has a positive potential difference in a

direction away from the branch point. Negatively charged components will be driven into the second subsidiary channel under these conditions and blocked from entering the first subsidiary channel.

- 5 Embodiments of the present invention can be used to provide fast switching between collection channels for components with little cross-talk and thus precise collection of a component.

10 In an arrangement as just described, extremely good separation can be achieved between constituent molecular bands. At the moment of switching to apply the negative potential difference to the short section of the first subsidiary channel, a clean separation will be achieved between negatively charged components either side of the end of the short section. Negatively charged components which are still travelling within the short section will be driven back again to
15 the branch point while negatively charged components which have already travelled beyond the short section will continue along the subsidiary channel (or vice versa).

20 The separation device may be fabricated in different ways. For instance, it might be constructed using a channel structure microfabricated into a chip. Alternatively, it might be provided as a branched capillary structure. The fabrication technique is likely to affect the suitable dimensions of a device and thus terms such as "short section" and "in the region of the branch point" will mean slightly different things in different circumstances. Typically, where a
25 branched microchannel has been fabricated on a chip, these terms indicate a physical distance of the order of a few millimetres. In the case of the branched capillary structure, these terms indicate a physical distance of the order of a few

centimetres. However, it is expected that these distances will substantially reduce in the future, as the technology develops and it becomes commercially realistic to produce channels of sub-micrometre sizes. In current systems, switching typically takes place within milliseconds (depending on the speed of the components to be separated, and the resolution required). The components may, for example, be between 1 and 50 μm apart.

The switchable voltage control means may be adapted, on switching, to reverse the polarity of the potential differences along each of two subsidiary channels at a branch point so that any one subsidiary channel can be selected to be subject to a different polarity from every other subsidiary channel at that branch point. Such an arrangement supports the separation of charged components into different respective subsidiary channels where there are several subsidiary channels at one branch point. Only one subsidiary channel should show a different polarity at any one time, in order to collect a component into it, but the subsidiary channel selected for collection of each component can be rotated through several available options at one branch point.

The voltage control means may conveniently be provided with a timer for use in controlling voltage in accordance with measured migration behaviour along the feed channel of the components to be separated. As long as the migration behaviour of a component it is desired to collect is known, it becomes possible to use such a timer for automated collection.

Alternatively or additionally, the voltage control means may be provided with a detector for use in controlling voltage, the detector being adapted to detect migration behaviour along the feed channel of at least one component to be

separated. The use of a detector allows real time behaviour of a component to be taken into account. For instance, fluctuations in migration behaviour due to temperature changes which could produce cross contamination in a timed system can be immediately responded to.

5

Different arrangements might be used for providing the voltage control in the region of a branch point. For instance, in a first arrangement the separating device might comprise a first voltage source, for connection to at least one subsidiary channel to produce a potential difference along the feed channel and
10 said at least one subsidiary channel, and a second voltage source for use by the voltage control means in the region of one or more branch points.

15

In a second arrangement, the separating device might comprise a voltage source for connection to all the subsidiary channels at the same time to produce a potential difference along the feed channel and each subsidiary channel, the
15 voltage control means comprising means for short circuiting a point along the feed channel to a point along at least one of the subsidiary channels, in the region of the branch point for that subsidiary channel. This second arrangement is particularly advantageous because it means it is not necessary to switch a
20 high voltage in order to change a subsidiary channel for collection of a component. This arises because the voltage source which is connected to produce a potential difference along the feed channel and at least one subsidiary channel is usually a high voltage source, designed to develop relatively quick differential migration of the components along the feed channel for collection
25 into a subsidiary channel. By using the short circuiting arrangement described, only lower voltages need be switched to achieve the change in local conditions

at a branch point which determine the direction taken by a component currently in the region of the branch point.

5 In a third arrangement, a separating device comprises a voltage source for connection to at least one subsidiary channel to produce a potential difference along the feed channel and said at least one subsidiary channel, wherein the voltage control means comprises a diode chain connected between the voltage source and earth, at least one subsidiary channel at a branch point being switchably connected to at least two alternative points in the diode chain so as
10 to provide first and second configurations, the potential difference along the subsidiary channel in the region of the branch point in the first configuration having opposite polarity to that potential difference in the second configuration.

15 According to a second embodiment of the present invention, there is provided a method of separating an electrically charged component from a mixture, by differential flow along a branched channel structure, the method comprising the steps of:

- (i) applying a force to the mixture so as to move the mixture along a main channel of a channel structure to a branch point connecting
20 the main channel to at least two branch channels; and
- (ii) applying an electrical potential difference to a portion of each branch channel in the region of the branch point, wherein the electrical potential difference applied to a selected branch channel presents a polarity at the branch point which is different from the
25 polarity presented at the branch point by an electrical potential difference applied to another branch channel at the said point.

The method may further comprise reversing the polarity presented by the electrical potential difference applied to the selected branch channel, and reversing the polarity presented by the electrical potential difference applied to
5 one other branch channel at the branch point, so as to change the selected branch channel from a first to a second branch channel.

A system for selecting the path of material flowing in an electrophoresis channel will now be described as an embodiment of the present invention, by
10 way of example only, with reference to the accompanying figures in which:

Figure 1 shows schematically a branched microchannel for use in electrophoresis;

Figure 2 demonstrates a problem which can occur with the branched microchannel of Figure 1;

15 Figure 3 shows schematically a set of connection points for use in applying a reverse voltage to the branched microchannel in order to avoid or ameliorate the problem of Figure 2;

Figure 4 shows schematically a Zener diode chain for use in the arrangement of Figure 3; and

20 Figure 5 shows an alternative arrangement for applying a reverse voltage using the connection points of Figure 3.

In electrophoresis, charged particles such as biomolecules move through a medium along a channel under the influence of an applied electric field. The
25 channel can for instance be microfabricated on a chip, or might be a branched capillary tube. A voltage difference is applied between the ends of the channel. Charged particles inserted into the channel at one end (determined by the

direction of the voltage difference and the effective charge of the particles) will move to the other end of the channel under the influence of the electric field. Particles having different characteristics move along the channel at different rates and thus mixed particles will separate into different groups as they move
5 along the channel. It is useful to be able to collect one or more separated groups of particles and this can be accomplished by using a channel with multiple branches and by switching the flow of particles among the different branches in a timed fashion. One possible configuration of branched channel is illustrated in Figure 1. Embodiments of the present invention can however be
10 applied to any configuration and number of branched channels.

Referring to Figure 1, a branched microchannel 100 for use in electrophoresis may comprise a generally "Y" shaped channel construction with means for applying a potential difference along it (not shown). A stem portion 105 is
15 earthed at one end. At the other end, it branches into two side channels 110, 115 and a voltage ("HV") can be applied at the end of either side channel, or both side channels, to produce a potential difference along the length of the microchannel 100. Typically, the channel defined by the stem portion 105 may be about 50 μ m wide and 200 μ m deep. But channels of far smaller dimensions
20 can be expected in the future, as the technology develops. The branch lines 110, 115 preferably have a combined cross sectional area which is approximately equal to that of the stem portion 105.

Although the point of the bifurcation is shown as being sharp in Figure 1, it
25 need not necessarily be so in a practical embodiment. In certain circumstances, it may be desirable for the bifurcation to be to a certain extent rounded.

If a sample containing charged particles of different types is introduced at the earthed end of the stem portion 105, it will migrate along the stem portion under the influence of the voltage. The particles of different types migrate at different speeds, forming constituent bands 120. When each constituent band reaches the branch point, it can be switched into either of the side channels 110, 115 by applying the voltage to the selected side channel. In Figure 1, it can be seen that some constituent bands 130 have previously reached the branch point and been switched into the right hand side channel 110 by applying the voltage according to CONDITION "R". However, the next constituent band 125 has reached the branch point and been switched into the left hand side channel 115 by applying the voltage according to CONDITION "L", thus separating it from the preceding bands 130.

As mentioned above, problems can arise at the point of switching from the CONDITION "R" configuration to the CONDITION "L" configuration (or vice versa). It can be difficult to get clean separation of one constituent band from the next. Firstly for instance, it is possible that particles in the leading edge of a constituent band 120 still approaching the branch point start to travel up the wrong side channel. Secondly, it is possible that particles in the trailing edge of a constituent band 130 already travelling up a side channel come under the influence of the switched voltage and migrate back to the branch point and into the wrong side channel. Figure 2 shows a charged particle 200 in such a trailing edge. If the voltage is switched from the CONDITION "R" configuration to the CONDITION "L" configuration, this particle and its near neighbours are still very close to the branch point and can change direction, migrating back to the branch point and into the left hand side channel 115, thus contaminating the constituent band 125 now being collected in the left hand

side channel 115. The transport of the molecules from one side channel to another, as shown in Figure 2, may be facilitated if the bifurcation point is slightly rounded (rather than being sharp as schematically illustrated in the drawing).

5

In embodiments of the present invention, contamination of this type can be reduced or avoided by applying a locally reversed voltage to any side channel not selected for collecting a constituent band. That is, a reversed voltage can be applied to a short portion of any non-selected channel which adjoins the branch point. Each time a different side channel is selected for collection of a constituent band, the reversed voltage is taken off the newly selected side channel and applied to a side channel which has been deselected. Alternatively, the reversed voltage may be applied temporarily, just during the period of switchover from one channel to another when there is the most significant risk of contamination occurring. The required period for this temporary switch condition can be pre-calculated according to the known or discovered mobilities and the needs of the case at hand: sometimes greater purity is desirable and a longer switch period can be applied.

10

15

20

25

The following is a description of a system for selecting the path of biological material flowing in an electrophoresis channel. This material may comprise for example nucleic acids such as deoxyribonucleic acid (DNA) and ribonucleic acid (RNA) or proteins in the form of peptides, protein digest fragments or any other form of proteinaceous material. Selection of any one or more particular fragment or band of material is accomplished primarily by using a branched microchannel 100 as shown in Figure 1 and applying the voltage "HV" to the end of a selected side channel 115 for collection of the fragment or band 125

currently reaching the branch point between the two side channels 110,115. As soon as that fragment or band 125 is wholly collected in the selected side channel 115, the voltage "HV" is switched back to the end of the other side channel 110.

5

In order to reduce or avoid the contamination risk mentioned above, a reverse voltage drop is applied at the entrance to all non-selected branches. The reverse voltage drop can be applied at all times or just in the period immediately after a switch of the voltage "HV".

10

It should be noted that although only two side branches 110, 115 are shown in Figures 1 and 2, a switching system can be used so that flow can be directed down any one of a more complex configuration of channels. The reverse voltage is applied to every non-selected channel at a branch point so that molecules will migrate into only the selected side channel. Thus the principle can be extended to any branched structure by considering each branch point, which may have any number of branches coming from it, to be an instance of the singly branched structure. In another embodiment (not shown) there may be more than two channels at the or each bifurcation. By means of cascades and poly-furcations, very complex separating structures may be defined. Where required, previously-separated components may be selectively combined simply by merging together the resultant branch channels.

15
20

Referring to Figure 3, the reverse voltage drop is applied between a point "B" just before the branch point and a point "A" or "C" just past the entrance of the branches down which no flow is desired. This causes the direction of molecular flow to be reversed in that region, which means that no molecules flowing

25

toward the entrance to the side channel carrying the reverse voltage can enter, while any molecules which have progressed past the reversed section will continue to the end of the side branch that they are in.

- 5 To switch the molecules into the left hand side channel 115 as shown in Figure 3, the voltages at the points "A", "B" and "C" bear the following relationship:

$$A < B < C$$

- 10 To switch the molecules into the right hand side channel 110 as shown in Figure 3, the voltages at the points "A", "B" and "C" bear the following relationship:

$$C < B < A$$

- 15 The voltages can be applied in several different ways. One way is to use a fixed source of voltages and to switch these voltages, for instance between the points "A" and "C", to select different branches. An alternative is to use the intrinsic resistance of the channel and to connect points "A" or "C" directly to point "B".

- 20 Referring to Figure 4, the voltages can be switched rapidly using a Zener diode chain 400. To switch the molecules into the right hand side channel 110 (CONDITION "R"), the N_c switches are closed and to switch them into the left hand side channel 115 (CONDITION "L"), the N_o switches are closed. Alternatively, it would be possible to use independently-operated voltage sources.

- 25 Referring to Figure 5, another approach is to supply the voltage HV to both of the side channels 110, 115 and to short the points "A" and "B", or "C" and "B", appropriately. This is convenient, since lower voltages can be used. The

arrangement can be used with a constant current power supply, since the power drain is similar whichever side is chosen. That is of course not the case where a Zener diode chain 400 is used, such as that shown in Figure 4.

- 5 Typically, where the branched microchannel has been fabricated on a chip, the physical distance between the points "A" and "B" may be of the order of a few millimetres. As mentioned above, an alternative arrangement is a bifurcated capillary in which case the spacing between points "A" and "B" may be of the order of a few centimetres. However, it is expected that these lengths
10 may be very substantially reduced in future, as the technology develops.

The HV supply will normally be around +100 volts where the branched microchannel has been fabricated on a chip and up to +5000 volts for an embodiment using a bifurcated capillary.

15

The back-voltage applied between the points "A" and "B", or between "C" and "B", is of the order of tens of volts.

- A similar approach to any of those described above can be used to deal with
20 repeated bifurcations in the channels.

- If a detector is placed underneath the chip or the capillary, the movement of the constituent bands can be tracked in real time. It would then be possible to switch the voltages automatically, by computer, for example based on pattern
25 matching. So, if the computer noted that a particular sequence of bands was moving down towards the junction, it could selectively switch out certain bands into a side channel for further investigation while the rest of the sample

continues to pass down another channel. An arrangement such as that shown in Figure 5 lends itself particularly well to automated switching of this type since it is unnecessary to switch the higher "HV" voltage to achieve selection of a new side channel.

5

The invention is not limited to molecules flowing along channels by means of electrophoresis. In other embodiments, the molecules or other components to be separated may be urged along the channel by any suitable force, including although not limited to pressure, gravity, or centrifugal force.

10

It should be noted that the word "comprising" as used herein is intended to be broadly interpreted so as to include for instance at least the meaning of either of the following phrases: "consisting solely of" and "including amongst other things".

15

CLAIMS

1. A separating device for separating components flowing along a channel, the device comprising a main channel branched at a branch point connected to
5 at least two subsidiary channels, and switchable voltage control means for controlling a voltage in the region of the branch point to provide potential differences of opposing polarity along the subsidiary channels such that components to be separated are caused to flow from the main channel into a selected subsidiary channel.
- 10 2. A separating device according to Claim 1 wherein the switchable voltage control means is adapted, on switching, to reverse the polarity of the potential differences along each of two subsidiary channels at a branch point so that any one subsidiary channel can be selected to be subject to a different polarity from
15 every other subsidiary channel at that branch point.
3. A separating device according to either one of the preceding claims wherein the voltage control means operates in dependence upon the flow behaviour of the components to be separated.
- 20 4. A separating device according to claim 1 or claim 2 wherein the voltage control means is provided with a detector for use in controlling voltage, the detector being adapted to detect flow behaviour of at least one component to be separated.
- 25 5. A separating device according to any one of the preceding claims, wherein the main channel is branched at more than one branch point and the

voltage control means is adapted to control voltage in the region of each branch point independently.

- 5 6. A separating device according to any one of the preceding claims, comprising a first voltage source, for connection to at least one subsidiary channel to produce a potential difference along the main channel and said at least one subsidiary channel, and a second voltage source for use by the voltage control means in the region of one or more branch points.
- 10 7. A separating device according to any one of Claims 1 to 5, comprising a voltage source, for connection to all the subsidiary channels at the same time to produce a potential difference along the main channel and each subsidiary channel, and wherein the voltage control means comprises means for short circuiting a point along the main channel to a point along at least one of the
- 15 subsidiary channels, in the region of the branch point for that subsidiary channel.
- 20 8. A separating device according to any one of Claims 1 to 5, comprising a voltage source for connection to at least one subsidiary channel to produce a potential difference along the main channel and said at least one subsidiary channel, wherein the voltage control means comprises a diode chain connected between the voltage source and earth, at least one subsidiary channel at a branch point being switchably connected to at least two alternative points in the diode chain so as to provide first and second configurations, the potential difference
- 25 along the subsidiary channel in the region of the branch point in the first configuration having opposite polarity to the potential difference along the subsidiary channel in the region of the branch point in the second configuration.

9. A separating device according to any one of the preceding claims in which the channels are electrophoresis channels.
10. A separating device according to claim 1 in which at least one of the subsidiary channels is further branched, the device including a further switchable voltage control means for the device including a further switchable voltage control means for controlling a further voltage in the region of the further branch point.
11. A method of separating an electrically charged component from a mixture, by differential flow along a branched channel structure, the method comprising the steps of:
- (i) applying a force to the mixture so as to move the mixture along a main channel of a channel structure to a branch point connecting the main channel to at least two branch channels; and
 - (ii) applying an electrical potential difference to a portion of each branch channel in the region of the branch point, wherein the electrical potential difference applied to a selected branch channel presents a polarity at the branch point which is different from the polarity presented at the branch point by an electrical potential difference applied to another branch channel at the said branch point.
12. A method according to claim 11 which further comprises reversing the polarity presented by the electrical potential difference applied to the selected branch channel, and reversing the polarity presented by the electrical potential

difference applied to the said another branch channel at the branch point, so as to change the selected branch channel from a first to a second branch channel.

13. A method as claimed in claim 11 or claim 12 in which the said force is
5 generated by means of an electrophoretic potential.

14. A method as claimed in claim 11 or claim 12 in which the said force is generated by means of fluid pressure.

10 15. A method as claimed in claim 11 or claim 12 in which the said force is generated by means of gravity.

16. A method as claimed in claim 11 or claim 12 in which the said force is centrifugal.

1/3




FIGURE 1

CONDITION "R"

CONDITION "L"







FIGURE 2



2/3




FIGURE 3




FIGURE 4

3/3




FIGURE 5

INTERNATIONAL SEARCH REPORT

Internati Application No
PCT/GB 03/02926

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01N27/447 B01L3/00 B01D57/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01N B01L B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 61888 A (FU ANNE ;QUAKE STEPHEN (US); ARNOLD FRANCES (US); CALIFORNIA INST) 2 December 1999 (1999-12-02)	1-5,9-16
Y	page 6, line 14-17; figures 4A,4B,5,8 page 37, line 24 -page 39, line 6	6-8
Y	EP 0 816 837 A (CALIPER TECHN CORP) 7 January 1998 (1998-01-07) the whole document	6-8
A	WO 99 24827 A (UNIV CALIFORNIA) 20 May 1999 (1999-05-20) page 6, line 10-20	1-16

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

29 September 2003

Date of mailing of the international search report

09/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Müller, T

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No

PCT/GB 03/02926

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9961888	A	02-12-1999	AU 763433 B2	24-07-2003
			AU 4955799 A	13-12-1999
			CA 2333201 A1	02-12-1999
			EP 1190229 A2	27-03-2002
			JP 2002528699 T	03-09-2002
			WO 9961888 A2	02-12-1999
			US 6540895 B1	01-04-2003
			US 2002005354 A1	17-01-2002
EP 0816837	A	07-01-1998	US 5800690 A	01-09-1998
			AU 718697 B2	20-04-2000
			AU 3672497 A	21-01-1998
			BR 9710193 A	11-01-2000
			CA 2258699 A1	08-01-1998
			EP 1241472 A2	18-09-2002
			EP 0816837 A1	07-01-1998
			EP 0909386 A1	21-04-1999
			JP 2000513813 T	17-10-2000
			KR 2000022341 A	25-04-2000
			NZ 333438 A	25-08-2000
			WO 9800707 A1	08-01-1998
			US 6413401 B1	02-07-2002
			US 5965001 A	12-10-1999
			ZA 9705948 A	19-03-1998
WO 9924827	A	20-05-1999	US 6143152 A	07-11-2000
			AU 1312199 A	31-05-1999
			CA 2308366 A1	20-05-1999
			EP 1027596 A1	16-08-2000
			JP 2001523000 T	20-11-2001
			WO 9924827 A1	20-05-1999

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.